

SCOPE OF ACCREDITATION TO ISO/IEC 17025:2017

HOLO-KROME

61 Barnes Industrial Park North Wallingford, CT 06492 Ninos Moshi Phone: 203 284 7022

MECHANICAL

Valid To: September 30, 2022 Certificate Number: 1046.06

In recognition of the successful completion of the A2LA evaluation process, accreditation is granted to this laboratory to perform the following <u>fastener tests on steel and stainless steel</u>:

<u>Test:</u> <u>Test Methods:</u>

Case Depth ISO 2639; SAE J423

Decarburization ASTM F835, F912, F912M, F2328;

ISO 898-1, 898-5

Discontinuity (Visual) ASTM F788 (6.5.1.4); ISO 6157-1, ISO 6157-3

Hex Socket Strength ASTM F912, F912M; ISO 898-5, 3506-3

Microhardness

Vickers (200 gf and 500 gf) ASTM E384, E92

Proof (Bolts/Screws) ASTM F606/F606M (3.2.3); F606/F606M;

ISO 898-1

Rockwell Hardness (A, B, C, 30N) ASTM E18, A370, F606/F606M (3.1);

ISO 898-1

Sampling ASME/ANSI B18.18; ASTM F1470;

Per customer specification

Straightness ASME B18.2.9

Stress Durability (Hydrogen Embrittlement) NASM-1312-5; ASTM F606/F606M

Tensile (Axial/Wedge, Machined) ASTM A370, F606/F606M, E8; ISO 898-1

Visual Inspection ASME B18.18

Salt Spray ASTM B117

(A2LA Cert No: 1046.06) 10/21/2020

// Page 1 of 2

I. Dimensional Testing¹

Parameter	Range	$CMC^{2}(\pm)$	Technique/Method
Internal Socket ³	(0.050 to 1.00) in	N/A	Hex Go/No-Go/ASME B18.3
	(1.5 to 32) mm	N/A	Hex Go/No-Go/ASME B18.3.1M
Linear ³ –			
1D	Up to 1 in 6 in 8 in 12 in	0.00015" 0.0017" 0.0016" 0.0017"	Digital micrometer Calipers Calipers Calipers
2D	X axis: Up to 12 in Y axis: Up to 8 in	0.00073" 0.00068"	Optical comparator/manufacturer's manual
Threads (Sys 21) ³	#0 to 2 in	N/A	Rings/ANSI/ASME B1.2, B1.3
	M2 to M42	N/A	Rings/ANSI/ASME B1.16M

¹ This laboratory does not offer commercial dimensional testing service.

(A2LA Cert No: 1046.06) 10/21/2020

Page 2 of 2

² Calibration and Measurement Capability Uncertainty (CMC) is the smallest uncertainty of measurement that a laboratory can achieve within its scope of accreditation when performing more or less routine measurements of nearly ideal measurement standards or nearly ideal measuring equipment. CMCs represent expanded uncertainties expressed at approximately the 95 % level of confidence, usually using a coverage factor of k = 2. The actual measurement uncertainty of a specific measurement performed by the laboratory may be greater than the CMC due to the behavior of the customer's device and to influences from the circumstances of the specific measurement.

³ This test is not equivalent to that of a calibration.



Accredited Laboratory

A2LA has accredited

HOLO-KROME

Wallingford, CT

for technical competence in the field of

Mechanical Testing

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated April 2017).

SEAL 1978 SEAL 1978 A 2LA

Presented this 21st day of October 2020.

Vice President, Accreditation Services For the Accreditation Council

Certificate Number 1046.06

Valid to September 30, 2022